

gSKIN® MOUNT

Mounting Solution

FEATURES

- Optimized mounting solutions
- Excellent thermal properties
- Simple and fast mounting



MOUNT-1211



MOUNT-1212



MOUNT-1213



MOUNT-1214



MOUNT-1215

Product Name	gSKIN® MOUNT-1211	gSKIN® MOUNT-1212	gSKIN® MOUNT-1213	gSKIN® MOUNT-1214	gSKIN® MOUNT-1215
Article Number	A-018862	A-018871	A-018884	A-018891	A-018892
Product Type	Thermal Tape	Thermal Paste	Thermal Glue	Thermal Conductive Pad	Thermal Conductive Pad
Dimensions / Quantity	30mm x 30mm x 0.05mm (l x w x h) / 3 Tapes	3.5g	2 x 3.5g	30mm x 30mm x 0.5mm (l x w x h) / 3 Pads	30mm x 30mm x 3mm (l x w x h) / 3 Pads
Product Specifications	Thermally conductive and electrically insulating double-sided tape	Thermally conductive and electrically insulating paste	Thermally conductive and electrically insulating two component glue	Thermally conductive, colorless, non-adhesive pad	Thermally conductive, colorless, non-adhesive pad
Thermal Conductivity ^a [W/(mK)]	0.85	9.0	7.5	3	3
Thermal Resistance ^a [K/W]	0.814 ^b	0.056 ^b	0.066 ^b	1.67 ^c	10.00 ^d
Operating Temperature Range Min/Max [°C]	-20 / 120	-50 / 130	-40 / 150	-60 / 200	-50 / 200

^a Stated values from Supplier.

^b Assuming an area of 10mm x 10mm and a thickness of 0.05mm.

^c Assuming an area of 10mm x 10mm and a thickness of 0.5mm.

^d Assuming an area of 10mm x 10mm and a thickness of 3mm.

Datasheet V1.0, © Copyright greenTEG AG, 2016 All Rights Reserved